


This document is promulgated by the Department of Defense as the military standard to limit the selection of the item, product or design covered herein in engineering, design and procurement. This standard shall become effective not later than 90 days after the latest date of approval shown.

FED SUP CLASS  
5940

This document has been promulgated by the Department of Defense as the military standard to limit the selection of the item, product or design covered herein in engineering, design and procurement. This standard shall become effective not later than 90 days after the latest date of approval shown.



DASH NO	FINN	WIRE SIZE AVG NOM	STUD SIZE	A		B	C	D	E	F	G	H ±.003	K	L	M
				HOLE DIA MIN	HOLE DIA MAX										
1	MS-9371	6	6	.141	.153	5/32	5/16	1-1/8	1/8	15/16	5/16	.032	3/8	1/8	7/32

**MATERIAL:** COPPER, ANNEALED - SPECIFICATION QQ-C-576.

**FINISH:** HOT TIN DIP OR ELECTRODEPOSITED TIN ALL OVER, MINIMUM THICKNESS .0006 INCHES.

- NOTES:**
1. ALL DIMENSIONS IN INCHES. TOLERANCES: FRACTIONAL  $\pm 1/64$  UNLESS OTHERWISE SPECIFIED.
  2. REMOVE ALL BURRS.
  3. REFERENCED DOCUMENTS OF ISSUE IN EFFECT ON DATE OF INVITATION FOR BIDS SHALL APPLY.
  4. THE MS PART NUMBER CONSISTS OF THE MS NUMBER PLUS THE DASH NUMBER.

COORDINATING ORG SHIPS USAP	OTHER INT. A-SAG T E B-A OR Y N-	<b>MILITARY STANDARD</b>		<b>MS 35432</b>
		<b>TERMINAL LUG SOLDER TYPE, COPPER STAMPING, ONE HOLE, FLAT SLITTED.</b>		
MILITARY SPECIFICATION <b>MIL-T-15659</b>		COMMENTS:		QUANTITY 1    0    1

APPROVED 5 JULY 55 REVISED A 23 JULY 56